
EATION PUBLISHED UNDER THE PATENT O (12) INTERNATIONAL APP



(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 26 February 2004 (26.02.2004)

PCT

(10) International Publication Number WO 2004/016922 A2

(51) International Patent Classification7:

F02D

(21) International Application Number:

PCT/US2003/025481

(22) International Filing Date: 14 August 2003 (14.08.2003)

(25) Filing Language:

(26) Publication Language:

English

(30) Priority Data: 60/402,948

14 August 2002 (14.08.2002)

(71) Applicant (for all designated States except US): ATMO-SPHERIC SENSORS, LLC [US/US]; 416 East Church Road, King of Prussia, PA 19406-1533 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): MOSELEY, Patrick, T. [US/US]; 100 Ellsworth Place, Chapel Hill, NC 27516 (US).

(74) Agents: WRAY, James, C. et al.; 1493 Chain Bridge Road, Suite 300. McLean, VA 22101 (US).


(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FL GB, GD, GE, GH, GM. HR. HU, ID. H., IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD. SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA. UG, US, UZ, VC, VN, YU, ZA, ZM, ZW,

(84) Designated States (regional): ARIPO patent (GH. GM. KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM). European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FL FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO. SE, SI, SK, TR), OAPI patent (BE, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



and x indicates that the oxide can sustain a variable oxygen stoichiometry. A preferred general formulation is a single-phase perovskite structure $\Delta B_{1-Y}W_YO_X$ where y preferably lies between 0.03 and 0.15, more preferably between 0.05 and 0.10 and where x is close to 3. Preferred examples of compositions that can achieve these advantages include, but are not limited to, PrFe_{0.05}W_{0.05}O_x and LaFe_{0.05}W_{0.05}O_x.

Best Available Copy